



NOTE: ITEMS 11 AND 12 ARE ALSO PART OF REAR HUB AND DRUM ASSEMBLY, FIGURE 55.

ORD E64898

Figure 54. Front hub, drum assembly and related parts - exploded view

| (1) ILLUST | | (2) SOURCE, MAINT AND RECOVERABILITY CODE | | | | (3) FEDERAL STOCK NO | (4) DESCRIPTION | (5) UNIT OF ISSUE | (6) QTY INC IN UNIT | (7) 15-DAY MAINT ALW PER 100 EQUIP | |
|------------------|-------------------|---|---------------|-----------------------------|-----------------------|-----------------------------------|---|--------------------------------|-------------------------------------|--|--|
| (a) FIG NO | (b) ITEM NO | (a) MATERIEL CODE | (b) SOURCE | (c) MAINTENANCE LEVEL | (d) RECOVERABILITY | | | | (a) CO OR BTRY | (b) CO BN OR RECT | |
| | | | | | | | 13 - WHEELS | | | | |
| | | | | | | | <u>1311 - FRONT HUB DRUM ASSEMBLY AND RELATED PARTS</u> (Fig. 54) | | | | |
| 54 | 1 | | C | O | | 2520-737-5143 | CAP: hub (7375143) ----- | ea | 2 | | |
| 54 | 2 | | C | O | | 2530-291-7386 | PACKING, PREFORMED: front hub cap (65909-804821) ----- | ea | 6 | | |
| 54 | 3 | | C | O | | 5310-769-6521 | WASHER, KEY: front hub bearing nut (7696521) ----- | ea | 2 | | |
| 54 | 4 | | C | O | | 5310-769-6520 | WASHER, KEY: front hub bearing (7696520) ----- | ea | 2 | | |
| 54 | 5 | | P | O | | 3110-100-0532 | CUP, TAPERED ROLLER BEARING: mil-std-code 711-18520-1000 sr, si no. 2 tol, 1/16 in. back face corner rad, 2.8750 in. od, 0.5000 in. lg (706836) | ea | 4 | | |
| 54 | 6 | | C | O | | 2530-352-6962 | DRUM: brake (7328371) ----- | ea | 2 | | |
| 54 | 7 | | P | O | R | 2530-693-0792 | HUB: w/bearing cup, assy (8333378) ----- | ea | 2 | | |
| 54 | 8 | | P | O | | 5306-732-8294 | BOLT RIBBED SHOULDER: rivet type, S, carburized case harden, 1/2-20NF-3 rolled thd lh thd hub (7328294) | ea | 5 | | |
| 54 | 8 | | P | O | | 5306-732-8293 | BOLT RIBBED SHOULDER: rivet type, S, carburized case harden, 1/2-20NF-3 rolled thd rh thd hub (7328293) | ea | 5 | | |
| 54 | 9 | | P | O | | 5330-505-6700 | SEAL: oil, special type, 2-1/8 x 2.879 x 3/8 front hub (8329731) | ea | 2 | | |
| 54 | 10 | | P | O | | 3110-100-3526 | CONE: tapered roller bearing, mil-std-code 711-18590-3000 includes rollers and gage, sr, 1.6250 bore, 0.6875 w front hub (705423) | ea | 4 | | |
| 54 | 11 | | P | O | | 5305-013-3757 | SCREW, MACHINE: fl-hd, S, cd- or zn-pltd, 1/4-20UNC-2A x 3/8 (133757) | ea | 6 | | |
| 54 | 12 | | P | O | | 5310-523-2405 | NUT, CONE SEAT HEXAGON: S, cyanide case hardened, 1/2-20NF-2 rht wheel mounting hub (5232405) | ea | 5 | | |
| 54 | 12 | | P | O | | 5310-264-1929 | NUT, CONE SEAT HEXAGON: S, cyanide case hardened, parkerized, 1/2-20NF-2 lht wheel mounting hub (5232404) | ea | 5 | | |