



ORD E64896

Figure 52. Hydraulic lines and related parts

| (1) ILLUST | | (2) SOURCE, MAINT AND RECOVERABILITY CODE | | | | (3) FEDERAL STOCK NO | (4) DESCRIPTION | (5) UNIT OF ISSUE | (6) QTY INC IN UNIT | (7) 15-DAY MAINT ALW PER 100 EQUIP | |
|---|-------------------|---|---------------|-----------------------------|-----------------------|-----------------------------------|---|--------------------------------|-------------------------------------|--|-------------------------------|
| (a) FIG NO | (b) ITEM NO | (a) MATERIEL CODE | (b) SOURCE | (c) MAINTENANCE LEVEL | (d) RECOVERABILITY | | | | | (a) CO OR BTRY | (b) CO BN OR REGT |
| 12 - BRAKES - Continued | | | | | | | | | | | |
| <u>1204 - HYDRAULIC LINES AND RELATED PARTS (Fig. 52)</u> | | | | | | | | | | | |
| 52 | 1 | C | O | | | 2530-737-2836 | LINE: flexibly, front brake, assy 6 in. lg (7372836)----- | ea | 2 | | |
| 52 | 2 | C | O | | | 5340-371-4134 | CLIP, SPRING TENSION: lock flexible line to bracket (7735289) | ea | 4 | | |
| | 3 | C | O | | | | LINE: front tee to left flexible line tube, front tee to right flexible line tube, master cylinder to front hose tube, master cylinder tube (rear), rear tee to left wheel cylinder tube, rear tee to right wheel cylinder tube (8677344) | ea | 1 | | |
| | | P | O | | | 4730-014-2431 | Fabricated from: INVERTED NUT, TUBE, COUPLING: inverted flare, 45 deg seat, br, 3/8-24UNF-2A, 9/16 overall lg, 3/16 od tu front tee to left flexible line tube (2), front tee to right flexible line tube (2), master cylinder to front hose tube (2), master cylinder tube, rear (2), rear tee to left wheel cylinder tube (2) rear tee to right wheel cylinder tube (2) (142431) | ea | 12 | | |
| 52 | 4 | P | O | | | 4710-350-9886 | TUBING, COPPER: 3/16 od, 0.035 wall thk, 20-1/4 lg | ft | ≠ | | |
| | | C | O | | | 5340-696-0248 | CLIP: hose front axle brake line (2) and rear axle brake line (1) (68146-98382) | ea | 3 | | |
| 52 | 5 | C | O | | | 5340-737-2833 | CLIP: closed, brake line 5/16 in. line (7372833)----- | ea | 2 | | |
| 52 | 6 | C | O | | | 2530-737-2837 | LINE: flexible, rear axle tee to master cylinder line, assy 15 in. lg (7372837) | ea | 1 | | |
| 52 | 7 | C | O | | | 2530-495-8677 | GASKET: flexible, brake line tee fitting copper (7372834) | ea | 2 | | |
| 52 | 8 | C | O | | | 4730-737-2343 | TEE: rear axle brake line (7372343) ----- | ea | 1 | | |
| 52 | 9 | P | O | | | 5306-018-7263 | BOLT, ASSEMBLED WASHER: hex-hd, ext-teeth lock-washer, S, cd- or zn-pltd, 1/4-20UNC-2A x 7/8 (187263) | ea | 1 | | |
| 52 | 10 | P | O | | | 5306-042-3555 | BOLT, ASSEMBLED WASHER: hex-hd, ext-teeth lockwasher, S, cd- or zn-pltd, 1/4-20UNC-2A x 1-1/8 (423555) | ea | 1 | | |
| 52 | 11 | C | O | | | 2530-737-2839 | TEE: front axle crank line (7372839) ----- | ea | 1 | | |
| 52 | 12 | C | O | | | 2530-737-2835 | LINE: flexible, front axle to frame, assy 11 in. lg (7372835) | ea | 1 | | |
| 48 | 4 | C | O | | | 2530-703-2625 | GUARD: front brake flexible line (7032625) ----- | ea | 2 | | |
| <u>NON-ILLUSTRATED ITEMS</u> | | | | | | | | | | | |
| | | P | O | | | 4730-014-2431 | INVERTED NUT, TUBE COUPLING: inverted flare, 45 deg seat, br, 3/8-24UNF-2A, 9/16 in. overall lg, 3/16 in. od tu (142431) | ea | 4 | | |
| | | P | O | | | 5340-282-7551 | CLIP, CLOSED: 1/4 in od tube ----- | ea | 2 | | |
| | | P | O | | | 6Z19-471-2 | CLIP: fastener type E, S, 3/16 in. (side rail) (6Z1947-12) -- | ea | 4 | | |