



ORD E64896

Figure 52. Hydraulic lines and related parts

(1) ILLUST		(2) SOURCE, MAINT AND RECOVERABILITY CODE				(3) FEDERAL STOCK NO	(4) DESCRIPTION	(5) UNIT OF ISSUE	(6) QTY INC IN UNIT	(7) 15-DAY MAINT ALW PER 100 EQUIP	
(a) FIG NO	(b) ITEM NO	(a) MATERIEL CODE	(b) SOURCE	(c) MAINTENANCE LEVEL	(d) RECOVERABILITY					(a) CO OR BTRY	(b) CO BN SEP OR REGT
12 - BRAKES - Continued											
<u>1204 - HYDRAULIC LINES AND RELATED PARTS (Fig. 52)</u>											
52	1	C	O			2530-737-2836	LINE: flexibly, front brake, assy 6 in. lg (7372836)-----	ea	2		
52	2	C	O			5340-371-4134	CLIP, SPRING TENSION: lock flexible line to bracket (7735289)	ea	4		
	3	C	O				LINE: front tee to left flexible line tube, front tee to right flexible line tube, master cylinder to front hose tube, master cylinder tube (rear), rear tee to left wheel cylinder tube, rear tee to right wheel cylinder tube (8677344)	ea	1		
		P	O			4730-014-2431	Fabricated from: INVERTED NUT, TUBE, COUPLING: inverted flare, 45 deg seat, br, 3/8-24UNF-2A, 9/16 overall lg, 3/16 od tu front tee to left flexible line tube (2), front tee to right flexible line tube (2), master cylinder to front hose tube (2), master cylinder tube, rear (2), rear tee to left wheel cylinder tube (2) rear tee to right wheel cylinder tube (2) (142431)	ea	12		
52	4	P	O			4710-350-9886	TUBING, COPPER: 3/16 od, 0.035 wall thk, 20-1/4 lg	ft	≠		
		C	O			5340-696-0248	CLIP: hose front axle brake line (2) and rear axle brake line (1) (68146-98382)	ea	3		
52	5	C	O			5340-737-2833	CLIP: closed, brake line 5/16 in. line (7372833)-----	ea	2		
52	6	C	O			2530-737-2837	LINE: flexible, rear axle tee to master cylinder line, assy 15 in. lg (7372837)	ea	1		
52	7	C	O			2530-495-8677	GASKET: flexible, brake line tee fitting copper (7372834)	ea	2		
52	8	C	O			4730-737-2343	TEE: rear axle brake line (7372343) -----	ea	1		
52	9	P	O			5306-018-7263	BOLT, ASSEMBLED WASHER: hex-hd, ext-teeth lock- washer, S, cd- or zn-pltd, 1/4-20UNC-2A x 7/8 (187263)	ea	1		
52	10	P	O			5306-042-3555	BOLT, ASSEMBLED WASHER: hex-hd, ext-teeth lockwasher, S, cd- or zn-pltd, 1/4-20UNC-2A x 1-1/8 (423555)	ea	1		
52	11	C	O			2530-737-2839	TEE: front axle crank line (7372839) -----	ea	1		
52	12	C	O			2530-737-2835	LINE: flexible, front axle to frame, assy 11 in. lg (7372835)	ea	1		
48	4	C	O			2530-703-2625	GUARD: front brake flexible line (7032625) -----	ea	2		
<u>NON-ILLUSTRATED ITEMS</u>											
		P	O			4730-014-2431	INVERTED NUT, TUBE COUPLING: inverted flare, 45 deg seat, br, 3/8-24UNF-2A, 9/16 in. overall lg, 3/16 in. od tu (142431)	ea	4		
		P	O			5340-282-7551	CLIP, CLOSED: 1/4 in od tube -----	ea	2		
		P	O			6Z19-471-2	CLIP: fastener type E, S, 3/16 in. (side rail) (6Z1947-12) --	ea	4		